

M A T E R I A L S A F E T Y D A T A S H E E T

WHITE PIGMENT DISPERSION

Page: 1

PRODUCT NAME: WHITE PIGMENT DISPERSION
PRODUCT CODE: 514-001

HMIS CODES: H F R P
0 0 0 H

=====**SECTION I - MANUFACTURER IDENTIFICATION**=====

MANUFACTURER'S NAME: DURA TECHNOLOGIES, INC.
ADDRESS : 2720 SOUTH WILLOW AVE.
BLOOMINGTON, CA 92316

EMERGENCY PHONE : 800-424-9300 DATE PRINTED : 06/18/98
INFORMATION PHONE : 909-877-8477 NAME OF PREPARER : Richard Stewart

=====**SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION**=====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT PERCENT
		mm Hg @ TEMP		
DIMETHYL BENZENE (XYLENE) ACGIH TLV: 100PPM, : OSHA PEL 100 PPM	1330-20-7	5.1	68	0

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***
NOTE: A ZERO IN THE WEIGHT PERCENT COLUMN INDICATES THAT THERE IS LESS THAN ONE-HALF OF ONE PERCENT PRESENT.
WARNING | THERE ARE CERTIAN HEALTH HAZARDS INVOLVED WITH HANDLING AND STORING THIS MATERIAL. PLEASE READ AND FOLLOW THE SAPTY RECOMMENDATIONS PUT FORWARD ON THIS MSDS.

=====**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**=====

BOILING RANGE: 279 SPECIFIC GRAVITY (H2O=1): 2.14
VAPOR DENSITY: UNKNOWN EVAPORATION RATE: UNKNOWN
COATING VOC: 0.03 lb/gl
MATERIAL V.O.C.: 0.03 lb/gl

SOLUBILITY IN WATER: negligible
APPEARANCE AND ODOR: PIGMENT CONCENTRATE OF VARIOUS COLORS

=====**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**=====

FLASH POINT: 80 METHOD USED: TCC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1 UPPER: 6.6
EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG
SPECIAL FIREFIGHTING PROCEDURES

Wear full protective equipment including SELF-CONTAINED BREATHING APPARATUS. If water is used, fog nozzles are preferable. Water may be used to cool containers to prevent pressure build-up or autoignition. Water spray may be ineffective. WARNING: Burning liquid chemicals are usually lighter than water and will float spreading flames as the water flows from the site of the fire fighting efforts. WARNING!: Stay away from hot drums due to explosion hazard.

UNUSUAL FIRE AND EXPLOSION HAZARDS

At high temperatures this material may self polymerize. If polymerization occurs, there is the possibility of violent rupture of sealed containers. Styrene vapors are uninhibited and may form polymers in the vents or flame arrestors of storage tanks rendering them useless. These vents should be inspected frequently for blockage. Vapors may cause flash fires. Keep storage containers tightly closed and isolated from heat, electrical equipment, sparks and flames.

=====**SECTION V - REACTIVITY DATA**=====

STABILITY: STABLE
CONDITIONS TO AVOID

AVOID HEAT, Sparks or Flames. STORE MATERIAL IN A COOL DRY AREA IN TIGHTLY SEALED CONTAINERS.

INCOMPATIBILITY (MATERIALS TO AVOID)

Avoid contact with strong acids, oxidizers (bleaches), and strong bases (caustic soda).

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

If ignited this product will release carbon dioxide, carbon monoxide, and some organic acids. Do not breath fumes.

HAZARDOUS POLYMERIZATION: MAY OCCUR

=====**SECTION VI - HEALTH HAZARD DATA**=====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

The excessive inhalation of vapors may cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, and headaches. The symptoms of inhalation exposure are very similiar to common complaints caused by colds and other minor medical problems and must be monitored scrupulously to detect the appearance of overexposure.

M A T E R I A L S A F E T Y D A T A S H E E T

WHITE PIGMENT DISPERSION

Page: 2

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EYE CONTACT: This material can be irritating to the eyes. The symptoms of this are tearing, redness, and discomfort. SKIN CONTACT: This material may cause severe skin irritation. Symptoms include redness, burning drying and cracking.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Exposure by skin contact can cause severe skin irritation. Prolonged or repeated exposure may induce redness, burning, and cracking of the skin. Skin absorption is possible but no adverse effects are expected from this route of exposure under normal conditions of handling and use.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Swallowing can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of the liquid material can cause pneumonitis which can be FATAL. Care should be taken that such aspiration DOES NOT OCCUR SHOULD THE VICTIM VOMIT.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Reports have associated repeated or prolonged occupational exposure to solvents with permanent brain and nervous system damage, and liver or kidney atrophy. Intentional misuse by concentrating and inhaling the vapors can be fatal. This material has not been tested as a whole for health effects. WARNING! Although all intentional PROP 65 chemicals will be listed, THERE MAY BE DETECTABLE LEVELS OF UNINTENTIONAL CHEMICALS WHICH ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM PRESENT IN THIS PRODUCT.

TARGET ORGAN INFORMATION:

NO DATA

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: Yes
PROPOSITION 65: NO DATA

POLYESTER RESIN IS NOT KNOWN TO BE CARCINOGENIC.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Respiratory problems such as asthma; Skin disorders such as dermatitis; eye disorders or overly sensitive eyes.

EMERGENCY AND FIRST AID PROCEDURES

FOR ANY OVEREXPOSURE MOVE VICTIM TO FRESH AIR AND SEEK MEDICAL AID. EYE CONTACT: Immediately flush eyes with warm clean water. If symptoms persists seek medical attention. SKIN CONTACT: Immediately flush contaminated skin with water using mild soap if necessary. Remove all contaminated clothing and do not reuse clothes until thoroughly clean. INHALATION OVEREXPOSURE: Where breathing has stopped give artificial respiration. If breathing is difficult have qualified persons give medical oxygen. INGESTION: Give victim water to dilute chemical. NEVER induce vomiting in an unconscious or convulsing victim. aspiration of this material may occur during vomiting and can lead to lung damage or death. Seek immediate medical help

=====**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Evacuate personnel, remove sources of ignition, provide ventilation, equip cleanup crew with safty equipment, contain the spill with dikes, then use an absorbant or vacuum equipment to remove material. Store waste in a sealed container. Use only nonsparking tools during clean up. Do not allow this material to flow into the environment. If the spill exceeds the reportable quantity notify RPA and DOT officials.

WASTE DISPOSAL METHOD

THIS MATERIAL IS NOT KNOWN TO HAVE ANY CHARACTERISTICS OF HAZARDOUS WASTE NOR IS IT KNOWN TO CONTAIN ANY LISTED HAZARDOUS WASTE.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Do not store above 120 deg. F. Store large quantities in buildings designed to comply with Osha, EPA, and local fire department regulations. KEEP AWAY FROM HEAT, SPARKS AND FLAMES. Keep containers closed and upright when not in use to prevent the escape of fumes and liquid into the work or storage area.area. Inspect containers frequently to detect any possible damage or deterioration which might cause release of the material to the environment.

Polymerization of this coating during storage may cause the container to burst explosively. STORE IN COOL DRY AREA.

OTHER PRECAUTIONS

Containers should be grounded when the material is being transferred/mixed to prevent static build up. Empty containers retain all of the hazardous characteristics of the material itself and should be handled carefully untill they are thoroughly clean or destroyed. Large quantities of this material should be stored only in buildings which conform to OSHA standards. If any materials (such as

M A T E R I A L S A F E T Y D A T A S H E E T

WHITE PIGMENT DISPERSION

catalysts, colorants, or thinners) are added to this product read all relevant MSDS as the mixture will retain ALL of the hazardous characteristics of the chemicals added.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

During the application of this product or at any time vapors escape into the work space, exposed persons should use appropriate cartridge respirators (NIOSH/MSHA approved) or in instances of high concentrations, air provided breathing apparatus. Refer to OSHA regulations to maintain workplace safety. If respirators are required, employees must be trained to use the respirators, the fit of the respirator must be tested, and the employee's lung capacity must be tested for ability to use the respirator. Respiratory protection should be used during the curing, cutting, sanding, or polishing of this product. If Respirators are required they must be carefully selected according to the conditions present at customers location.

VENTILATION

Clean air dilution and local exhaust may be used to maintain the vapor concentration below current exposure limits and 20% below the LEL, except in confined areas where forced ventilation may be necessary. Refer to OSHA guidelines for handling these types of materials.

PROTECTIVE GLOVES

Solvent impermeable gloves should be worn to prevent physical contact with the product.

EYE PROTECTION

To protect your eyes, wear safety glasses with side shields, chemical goggles, or face shields.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Solvent impermeable, protective clothing should be worn to minimize skin contact with this product. Emergency showers and eye wash stations should be provided in the work space. Wear steel toed shoes when handling heavy objects.

WORK/HYGIENIC PRACTICES

Inspect Fire extinguishers at regular intervals. Keep work space clean. Retain safety features on all equipment.

===== SECTION IX - DISCLAIMER =====

To the best of our knowledge this MSDS is accurate. To the extent allowed by law, this statement is made in lieu of any other warranties, expressed or implied including but not limited to any implied warranty of merchantability or fitness for a particular purpose and is in lieu of any other obligations or liability on the part of DURALL PLASTICS, INC.